

DEFENSE

Aqeri

962483

Aqeri 962483 is a semi rugged 19" 3U Cisco-based Fiber and Copper Gigabit Switch with POE for Military and Industrial applications. Interface connectors, copper and fiber are IP54 sealed. The switch has been specially designed to withstand harsh environments where operators place high demand on function and reliability. It works reliably inspite of dust, dirt, vibrations, strong electromagnetic fields and standard temperature variations. Further, the fully aluminum construction stands for low radiation and high noise immunity.

Features:

- > Fully sealed all aluminum 19" 3U chassis
- > Based on Cisco WS-C3560X-24P-S Layer 3
- > 20 x Gigabit in RJ45 connectors
- > 4 x Gigabit SX Multimode in LC connectors
- > Integrated heating and climate control



TECHNICAL SPECIFICATIONS

Switchboard: Cisco WS-C3560X-24P-S Layer 3

I/O Interfaces

Gigabit: x20
PoE (7.5W / port): x10 of above interfaces
1000Mbit SX Multimode: x4
SNMP: x1
Console: x1

CONNECTORS

Gigabit: RJ45
PoE: RJ45
1000Mbit SX Multimode: LC
SNMP: RJ45
Console: RJ45
DC In: MS3102E 10SL-3P

PHYSICAL CHARACTERISTICS

Dimensions: 440 x 132.45 x 500mm (WxHxD)
Weight: 12 kg
Color: Green, other optional

ELECTRICAL SPECIFICATIONS

Power requirements: 48VDC
Power consumption: Max 110W at 48VDC (excluding heaters)

ENVIRONMENTAL CHARACTERISTICS

Designed to fulfill
(Other standards on request): European CE, EN 60950-1
Optional: MIL-STD-461E
MIL-STD-1275B
MIL-STD-810G
TEMPEST SDIP-27 Level A, B, C: Option
Temperature Operating: 0°C to +40°C
Vibration Operating: 10-500Hz 1,04g rms
Shock Operating: 15g, 11ms, ½ sine wave
Humidity: 5% to 95% non condensing
Altitude Operating: 3000m

We reserve the right to change the information of this document without further notice. 110901