

DEFENSE

Aqeri

98213

4U Router

Aqeri 98213 is a military router based on Cisco 2821-HSEC/9. It is equipped with Cisco modules for Ethernet, FXS, V35, ISDN etc. The unit has internal climate control for use in a wide temperature area and a temperature monitoring port for alarm output. Further, the router has an internal redundant AC power unit.

Features:

- > 19" 4U semi-sealed chassis
- > Redundant 90-264 VAC-in power, 50-60 Hz
- > Temperature monitoring
- > Interfaces for Ethernet, FXS, V35, ISDN, console, etc.



TECHNICAL SPECIFICATIONS

Router Board: Cisco 2821-HSEC/9

I/O Interfaces

10/100 Mbit: x2
FXS: x2
V.35: x2
ISDN: x1
Aux: x1
Console: x1
Temp Monitoring: x1

CONNECTORS

10/100 Mbit: MIL 38999
FXS: MIL 38999
V.35: MIL 38999
ISDN: MIL 38999
Aux: DSUB
Console: DSUB
Temp Monitoring: MIL 38999
AC In: MIL 38999

PHYSICAL CHARACTERISTICS

Dimensions: 440 x 177 x 504mm (WxHxD)
Weight: 17 kg
Color: Green, other optional

ELECTRICAL SPECIFICATIONS

Power requirements: 90-264 VAC, 50-60Hz (Internal Redundant Power Supply)
Power consumption: 110W (excluding heaters)

ENVIRONMENTAL CHARACTERISTICS

(Other standards on request): MIL-STD-461E
MIL-STD-810G
European CE
TEMPEST SDIP-27 Level A, B, C: Option
Temperature Operating: -20°C to +55°C
Vibration Operating: 20-2000Hz 0,04g rms
Shock Operating: 40g, 6ms, ½ sine wave
Humidity: 5% to 95% non condensing
Altitude Operating: 3000m

We reserve the right to change the information of this document without further notice. 110831